CORNER DESCRIPTION

	\ I \ T	1 10
TOWNSHIP: 26 NORTH RANGE: 4 EAST		
CORNER LOCATION : NORTHWEST CORNER SECTION 7	1 1	6
DATE: 01/31/2007 PROJECT NO: STPD 15-4 (116)	1	
DESCRIBED BY: S. WESSEL CONTROL NO. 31434		
COUNTY: WAYNE STATE: NEBRASKA	12	7
NAME OF PROJECT: WAYNE NORTH	R 3 E	R4E
		11 7 6

DESCRIPTION OF CORNER:

CUT "X" IN NEW CONCRETE FROM PRE-CONSTRUCTION TIES.
FOUND 3/4 INCH PIPE 3.5 FEET BELOW ASPHALT AND 0.3 FEET WEST OF
CENTERLINE JOINT AFTER MILLING OF ASPHALT ON 10/03/2006. ON
05/24/2006, PRIOR TO CONSTRUCTION FOUND, 5/8 INCH PIPE (PIN) SET
BY BRUSH NOVEMBER 8, 1968 WHICH WAS 0.75 FEET NORTH AND 2.40
FEET EAST OF CORNER.



HISTORY OF CORNER:

ROBERT JONES IN SURVEY DATED SEPT. 23, 1901, BOOK 2, PAGE 325, RECORDS IRON IN MOUND. ROBERT JONES IN SURVEY DATED AUGUST 1929 RECORDS $\frac{3}{4}$ x 16 INCH PIPE, BOOK 2, PAGE 48. CYRUS JONES IN SURVEY DATED JULY 11, 1938 RECORDS IRON PIPE, BOOK 2, PAGE 110. NDOR PROJECT 4 (3) OF 1940 RECORDS CORNER 0.9 FEET WEST OF CENTERLINE. BRUSH INCORRECTLY SET A $\frac{5}{8}$ x 8 INCH PIN 1.5 EAST OF CENTERLINE "ACCORDING TO BEST AVAILABLE EVIDENCE" IN SURVEY DATED NOV. 8, 1968, BOOK 3, PAGE 74.

DESCRIPTION OF TIES:

DLAND

82.31 FEET EAST TO P.K. NAIL IN CONCRETE JOINT, SET 332.57 FEET EAST TO P.K. NAIL IN CONCRETE JOINT, SET 34.80 FEET WEST TO P.K. NAIL IN CONCRETE JOINT, SET P.K. NAILS ON LINE WITH CORNER 64.24 FEET SOUTHWEST TO CENTER OF MANHOLE LID 99.46 FEET NORTHWEST TO WATER VALVE 66.78 FEET NORTHWEST TO CENTER OF MANHOLE LID 15.75 FEET WEST TO CENTER LINE JOINT IN NEW PAVEMENT, HIGHWAY 15

PLANE	X =		MODIFIED	X =	
COORDINATE	ES Y =		COORDINATES	Y =	
OENTS	-n	T NEW -			
CENTE MANHO	DLE LID —	CONC			~ 1
		لبي			

